High Speed HOG

Model HHB-5000 Model HHB-10000 Model HHB-5000RA Model HHB-10000RA

Straight-Thru, Track Mountable, and **Right Angle Models available**

Key Features

- · Bevels tubes in seconds
- · Hand Held or Track Mountable with adjustable depth stop ensures uniform beveled tube ends
- Pilot automatically locates and centers tool on pipe or tube I.D.
- No clamping and no torgue reaction to operator
- Cutter blades have multiple cutting edges and require no fluids
- · Straight thru and right angle models
- · Tooling is interchangeable with all High Speed models
- · Fast, accurate and easy to use
- · Field proven, tough and boilermaker approved

No Clamping Required

MILLHOG[®] High speed tube bevelers feature a pilot locating system that automatically centers the tool on the tube. Simple to operate, just insert the pilot into the I.D., squeeze the throttle and finish your end prep completely in as fast as 3 seconds. The high speed cutting action creates no reaction torque, even if the tool is stalled.

Straight-Thru and Right Angle Models

The straight-thru models can be hand-held or used with the Track Chassis and Post Assembly. With this option bevel height is controlled with the adjustable depth stop and ensures all bevels are exactly the same height, saving valuable fit-up time. Right angle models are ideal for applications with height restrictions.



Cutterheads

	·				·				
Cutterhead	Si	ze	O.D. Dir	nension	Max. Tu	ibe O.D.	Min T	ube I.D	Insert
Part #	in	mm	in	mm	in	mm	in	mm	Size
1050-01	1.250	31.76	1.600	40.64	1.250	31.76	.450	11.43	.500
1050-02	1.500	38.10	1.850	47.00	1.500	38.10	.700	17.78	.500
1050-03	1.750	44.45	2.100	53.34	1.750	44.45	.700	17.78	.625
1050-04	2.000	50.80	2.350	59.69	2.000	50.80	.950	24.13	.625
1050-05	2.250	57.15	2.600	66.04	2.250	57.15	1.200	30.48	.625
1050-06	2.500	63.50	2.850	72.39	2.500	63.50	1.450	36.83	.625
1050-07	2.750	69.85	3.100	78.74	2.750	69.85	1.700	43.18	.625
1050-08	3.000	76.20	3.350	85.09	3.000	76.20	1.950	49.53	.625
1050-09	3.250	82.55	3.600	91.44	3.250	82.55	2.200	55.88	.625
1050-10	3.500	88.90	3.850	97.79	3.500	88.90	2.450	62.23	.625
1050-11	3.750	95.25	4.100	104.14	3.750	95.25	2.700	68.58	.625
1050-12	4.000	101.60	4.350	110.49	4.000	101.60	2.950	74.93	.625

Specifications: High Speed MILLHOG®

	HHB-5000	HHB-5000RA	HHB-10000	HHB-10000RA			
Working Range	.450in (11.43 mm)	.450in (11.43 mm)	.450in (11.43 mm)	.450in (11.43 mm)			
to	2.250in (57.15 mm)	2.250in (57.15 mm)	4.00in (11.43 mm)	4.00in (11.43 mm)			
Motor, pneumatic	1.5 hp (1118.55 W)	1.5 hp (1118.55 W)	3 hp (2237 W)	3 hp (2237 W)			
Air Pressure	91 psi (6.2 bar)	91 psi (6.2 bar)	91 psi (6.2 bar)	91 psi (6.2 bar)			
Air Volume	50 cfm (1416 lt/min)	50 cfm (1416 lt/min)	80 cfm (2265 lt/min)	80 cfm (2265 lt/min)			
Speed	5,000 rpm	5,000 rpm	10,000 rpm	10,000 rpm			
Clearance	1.5in (38.1 mm)	1.9in (48.26 mm)	2.125in (54 mm)	2.5in (63.5 mm)			
Working weight	9 lbs (4.1 kg)	8 lbs (3.63 kg)	14 lbs (6.4 kg)	13 lbs (5.9 kg)			
Shipping weight	40 lbs (18.2 kg)	40 lbs (18.2 kg)	45 lbs (20.4 kg)	45 lbs (20.4 kg)			
Track mountable	yes	no	yes	no			
Shipping Dimensions	27in x 18in x 7in (666 mm x 457 mm x 177 mm)						



High Speed Bevelers bevel tubes in seconds, no clamping required, the pilot locates and centers the tool on the tube I.D.



Right angle models fit limited access areas.

HHB-5000 Straight-Thru

Pilots center the tool and keep it

square to the tube. A properly sized

pilot is .015" to .030" under the tube

LD This tolerance ensures smooth

operation, long blade life and chatter free bevels.

HHB-



The Track Chassis and Post Assembly's adjustable depth stop ensures all tubes are beveled to the same height.



Carbide cutter inserts are available with two or four cutting edges and in two sizes

esco tool • 75 October Hill Road • Holliston, MA 01746 USA • 1.508.429.4441 • fax 1.508.429.2811 • email: millhog@escotool.com Available for Sale or Rent • www.escotool.com

Cutterheads hold the carbide cutter inserts and pilot and can be changed as needed for various tube

HHB-5000RA

Right Angle

and pipe sizes.